



WESTERN SCALE CO. LTD.

Western Scale Co. Ltd.
1670 Kingsway Ave.
Port Coquitlam, B.C.
Canada V3C 3Y9

Tel: 1.604.941.3474
Fax: 1.604.941.4020
Email: info@westernscale.ca
Web: www.westernscale.ca

M1 BASIC INDICATOR

Fast weights. Loads of features. Great price.

The M1 is an entry level indicator that is easy to use and adaptable to a wide variety of weighing applications. Lots of extras under the hood.

FEATURES

- Large LED Display & annunciators
- 5 button membrane keypad
- DYNArrest Vibration Filtering System for remarkably fast, stable readings in high vibration (industrial) areas
- 2 Serial ports
- Easy to navigate User & Calibration Menus
- Password and Category 1 Audit Trail system
- Programmable Weigh Tickets & Macros
- 4 or 6 wire load cell connections (jumper)
- Time & Date
- Mounting bracket



SPECIFICATIONS

POWER REQUIREMENTS

- 100-240 VAC 50/60 Hz
- Consumption: 40 mA (10 W)

EXCITATION

- 5 VDC. Up to 4 350 Ω or 8 700 Ω load cells

ANALOG INPUT RANGE

- 0-19 mV

RESOLUTION

- 1,000,000 internal A/D counts
- Up to 20,000 displayed divisions (LFT).
- Up to 100,000 (NLFT).

MEASUREMENT RATE

- 80 weight samples/second dependent on filter settings.

ANALOG SIGNAL SENSITIVITY

- .3 μ V

SYSTEM LINEARITY

- 0.01% of Full Scale

COMMUNICATIONS

- 1 full duplex RS-232 serial port
- 1 transmit only RS-232 serial port
- Fully configurable data format and selectable output strings.
- Wireless Communication Module (Optional)

RFI PROTECTION

- Filtered Excitation, Signal, and Sense lines

KEYPAD

- Membrane keypad: 5 keys

DISPLAY

- 7/8" (22 mm) LED display
- 6 digits (7 segments each)

ENCLOSURE

- 304 stainless steel with bracket
- Tough, dependable, and weather resistant

DIMENSIONS (Approx.)

- 9" x 5.5" x 3" (230mm x 140mm x 76mm) w/ bracket

WEIGHT (Approx.)

- 3.5 lb (1.6 kg)

OPERATING TEMPERATURE

- 14°F to 104°F (-10°C to 40°C)

APPROVALS

- NTEP Class III/IIIL (10,000): 09-012
- Measurement Canada Class III (10,000) / IIIHD (20,000): AM-5734

WARRANTY

- 2 year standard warranty