

# RoughDeck® QC Quick Clean


STAINLESS STEEL  
FLOOR SCALE



**LB** Les Balances  
**LEDUC & THIBEAULT**

# RoughDeck® QC Quick Clean

## STAINLESS STEEL FLOOR SCALE



The rugged design incorporates 304 stainless steel construction and four welded seal load cells with PTFE cable designed for high temperatures and washdown areas.



Dual corner locks secure the deck to the base for safety, durability, and convenience.

Unique dual gas-shock design provides easy opening and gentle closing.



Known as the toughest, most accurate floor scale line in existence, the RoughDeck's legendary performance is now customized for food, chemical and other frequent washdown applications.

RoughDeck QC is the weighing solution for efficiency and safety when cleaning cycles are tight. Our exclusive gas-shock design offers easy lifting, but even more importantly, eliminates dangerous slamming of the deck when closing. For added safety and convenience, a manual support bar swings into action during extended underdeck cleaning.

Legendary RoughDeck performance, innovative specialty features—the ultimate washdown solution.



### Standard Features:

- Rugged washdown design
- Smooth, 304 stainless steel top deck
- Four stainless steel welded seal shear beam load cells
- Rigid 304 stainless steel tube frame
- Remote EL604 stainless steel NEMA 4X junction box
- Four adjustable stainless steel SUREFOOT support feet
- 20 ft of SURVIVOR® hostile environment load cell cable to connect an indicator to the junction box
- Safety bar

### Options/Accessories:

- Stainless steel deck with treadplate
- Floor stand for indicator. Stainless steel, 36.3" high, and fits IQ plus® 355, IQ plus® 390-DC, IQ plus® 510, IQ plus® 590-DC and IQ plus® 710

### Specifications:

- End Load Capacity:** 100% full scale  
**m/V Output:** 1.50-1.87 mV/V nominal  
**Remote J-Box:** Stainless steel NEMA 4X enclosure can be located up to 10 ft away from the scale  
**Warranty:** 5-year limited warranty



CC# 92-001A5  
 $n_{max} = 5,000$   
 Class III

Shown with optional treadplate stainless steel deck.



### Dimensions/Capacities:

SIZE	CAPACITY LB (KG)	SHIP WT LB
2.5' x 2.5'	2000 lb (1000 kg)	158 lb
3' x 3'	2000 lb (1000 kg)	208 lb
4' x 4'	2000 lb (1000 kg)	338 lb
4' x 4'	5000 lb (2500 kg)	338 lb
4' x 4'	10,000 lb (5000 kg)	447 lb
4' x 5'	2000 lb (1000 kg)	406 lb
4' x 5'	5000 lb (2500 kg)	406 lb
4' x 5'	10,000 lb (5000 kg)	540 lb
4' x 6'	2000 lb (1000 kg)	477 lb
4' x 6'	5000 lb (2500 kg)	477 lb
4' x 6'	10,000 lb (5000 kg)	637 lb
5' x 5'	2000 lb (1000 kg)	478 lb
5' x 5'	5000 lb (2500 kg)	478 lb
5' x 5'	10,000 lb (5000 kg)	637 lb
5' x 7'	2000 lb (1000 kg)	705 lb
5' x 7'	5000 lb (2500 kg)	705 lb
5' x 7'	10,000 lb (5000 kg)	908 lb

Each scale is corner calibrated at the factory. Distributors must calibrate scale and indicator together.



Choose from a versatile line of digital weight indicators.

450.691.2111 (Beauharnois)  
 514.239.7060 (Montréal)  
 613.794.4133 (Ottawa)  
 1.877.691.2111 (Sans Frais)  
 info@leduc-thibeault.com

**Les Balances**  
**LEDUC & THIBEAULT**

Les Balances LEDUC & THIBEAULT Inc.  
 200 Robert McKenzie  
 Beauharnois, Qc J6N 0N9 • Canada  
 TEL: 450-691-2111

www.leduc-thibeault.com